

Cisco Desk Phone 9800 Series



Contents

03	Product overview
04	Features and benefits
06	Platform support
06	Product specifications
19	Ordering information
22	Licensing
22	Warranty information
22	Product sustainability
24	Cisco Capital
24	For more information



Product overview

Product description

Cisco is bringing a new standard to desk phones with a portfolio built for working in modern office environments. The Desk Phone 9800 Series was designed with IT and facilities in mind to deliver five new phone models and one Key Expansion Module (KEM). Included on each phone is the newly released PhoneOS software that simplifies the user experience and compliments our video portfolios RoomOS devices to give a seamless experience from desk spaces to meeting rooms. With expanded functionality – the 9800 Series combines secure enterprise calling, meetings, desk reservations, sustainability, and emergency notifications all in one device. You don't need to buy a

dedicated device for each feature – all the features are built into each phone.

The Desk Phone 9800 Series reduces the complexity of purchasing, deploying, managing, and training. To further simplify, you can use one device for Cisco Unified Communications Manager (CUCM), Webex Calling, Broadworks, or other 3rd party cloud calling platforms. Alongside our extensive portfolio of desk devices, the 9800 series is uniquely positioned in the market to help transform the workplace by bridging the gap between hybrid work, calling, and meetings – and is the most cost-effective solution for workstations at scale.



Features and benefits

Table 1. Features and benefits

FEATURE	BENEFIT
One platform with PhoneOS	<ul style="list-style-type: none"> • One device and one software configured for all platforms - such as Cisco Unified Communications Manager (CUCM), Webex Calling, Broadworks, or other 3rd party cloud calling platforms. • Deployments and setup easier for IT teams with the flexibility they require, providing a low-touch seamless experience to replace an existing phone with the 9800 series.
Desk reservation and hot desking	<ul style="list-style-type: none"> • Desk reservation and hot desking allow your organization to make the most of office real estate. People using shared workspaces can reserve, book, and sign into a desk for the day via their phone. • Native sign-in/authentication to enable users to personalize their space by accessing their contacts, calendar, meetings, and personalized settings. (not applicable for 9811)
Action button	<p>Each phone includes a customizable action button designed for a variety of use cases:</p> <ul style="list-style-type: none"> • Instantly access essential scenarios such as emergency alerts, security, broadcast/paging and more. • Configure up to three scenarios on a single action button for greater flexibility. • Execute multiple actions with a single action button trigger. For example, initiate a phone call while launching a remote web application to send text messages to a group of contacts. • Enable advanced interoperability with web applications through adaptable configuration fields.
Enhanced audio features including noise removal	<ul style="list-style-type: none"> • AI-based Background Noise Removal (BNR) for outgoing audio ensures clear communication for the person on the other end. (9841, 9851, 9861, and 9871) • On the other hand, AI-based Noise Removal for incoming audio actively reduces background noise from the caller's environment, delivering clearer sound to the end user. (9861 and 9871) • Enhances audio quality with AI by converting narrowband audio to wideband, making voices sound richer and more natural. (9861 and 9871) • Built-in speaker is enhanced by a larger speaker driver and new bass-enhancing acoustic enclosure for more real, natural-sounding voices.
One button to join a meeting	<ul style="list-style-type: none"> • Experience One Button to Push (OBTP) to quickly join meetings from the device's screen (applicable when registered to Webex Calling and CUCM). (not applicable for 9811)

Table 1. Features and benefits

FEATURE	BENEFIT
Webex Companion	<p>With the Webex desktop app and Cisco Desk Phone 9800 Series Companion, the end users can:</p> <ul style="list-style-type: none"> • Enable video and view or share content via the Webex desktop app while keeping audio on the desk phone during a call when registered to CUCM, or during a Webex meeting when registered to Webex Calling. • Better control of the desk phone via the Webex desktop app: mute/unmute and adjust the phone volume (applicable when registered to Webex Calling). (not applicable for 9811)
Security	<ul style="list-style-type: none"> • Security is at the core of design with hardware-enabled security, runtime protection, application security, and industry compliance • Featuring Trusted Platform Module (TPM) 2.0 hardware (not applicable for 9811; and SUDI on 9811 is protected by the SoC chip), plus top-of-the-line security features such as TLS 1.3, Secure Boot, Image Authentication, and more.
Serviceability	<ul style="list-style-type: none"> • View detailed issues and diagnostics information on the phone UI. • Built-in ThousandEyes Endpoint Agent on the 9861 and 9871 enabling network path monitoring.
Sustainability	<ul style="list-style-type: none"> • Leader for sustainable phones in the industry. • Over 77% PCR on 9811; over 74% PCR on 9841, 9851, 9861 and 9871 • 100% Recyclable packaging • Supports advanced sustainability features, incl. display off and deep sleep modes, smart power, carbon emission insights and reporting, etc. • Cisco takeback program which reduces e-waste and ensure that plastics can go back into recycled supply chain practices.
Language AI	<p>Enhance user experience with a Large Language Model:</p> <ul style="list-style-type: none"> • Enable live captions that allow users to view real-time transcriptions of dialogue during Webex meetings and calls. • Display in-meeting summary and highlight action items during a Webex meeting. This feature is especially beneficial for participants joining midway, helping them stay informed and focused.
Accessibility	<ul style="list-style-type: none"> • Voice Feedback, which is supported in English, French, Italian, German and Spanish, assists people with vision impairments by providing voice prompts for phone navigation, caller ID, button functions, and more. • Adjustable font size makes text easier to read and navigate.

Platform support

Table 2. Cisco Desk Phone 9800 series backend calling server support

PLATFORMS SUPPORTED	CERTIFICATIONS
Cisco Webex Calling	Interoperability Tested and Certified
Cisco Unified Communication Manager (CUCM)*	Interoperability Tested and Certified
Webex Dedicate Instance (DI)	Interoperability Tested and Certified
Cisco BroadWorks	Interoperability Tested and Certified
Microsoft SIP Gateway	Microsoft SIP Gateway Compatible
Asterisk	Interoperability Tested and Certified

* The 9811 is supported on UCM version 14 or above, whereas other 9800 Series models are supported on UCM version 12.5 or above. Native support for the Cisco Desk Phone 9800 Series is not available on all CUCM versions; a device package may be required.

Product specifications

Table 3. Product specifications

FEATURES	SPECIFICATIONS
Display	<ul style="list-style-type: none"> 9811: 2.6-inch Grayscale LCD, 256x132 resolution 9841: 3.5-inch Grayscale LCD, 384 x160 resolution, backlit 9851: 3.7-inch Color LCD, 480 x 240 resolution, backlit 9861: 5-inch Color LCD, 800 x 480 resolution, backlit 9871: 5-inch Color Touch LCD, 1280 x 720 resolution, backlit 9800 KEM: 5-inch Color LCD, 480 x 800 resolution, backlit
Audio (*may vary depending on the codec)	<ul style="list-style-type: none"> Frequency response: 100 Hz – 20 kHz for handsfree speaker FEC (Forward Error Correction) AEC (Acoustic Echo Cancellation) AGC (Automatic Gain Control) CNG (Comfort Noise Generation) VAD (Voice Activity Detection) PLC (Packet Loss Concealment) Silence Suppression* Acoustic Shock Protection (Handset/headset) Adaptive Jitter Buffer Dual Tone Multi-Frequency (DTMF) tone generation (RFC 2833 and in-band) Cisco HD audio, TIA-810/920 and ETSI ES 202 737/738/739/740 compliant

Table 3. Product specifications

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • Cisco smart audio <ul style="list-style-type: none"> - Conventional and AI based background noise and voice removal for sending side (9841, 9851, 9861 and 9871) - Conventional and AI based background noise removal for receiving side (9861 and 9871) - Enhances the in-call experience for PSTN calls by extending low-fidelity (narrowband) audio to high-definition (wideband) (9861 and 9871) • Ultrasonic support (9841, 9851, 9861 and 9871) • HAC (Hearing Aid Compatible) handset
Audio codec support	<ul style="list-style-type: none"> • OPUS, G.722, G.722.2, iSAC, G.711(a-law/μ-law), G.729a/b, and iLBC
Physical Line Keys	<ul style="list-style-type: none"> • 9811: 2 • 9841: 4 • 9851: 6 • 9861: 10 • 9871: N/A • 9800 KEM: 20 (2 pages)
Maximum of supported line and programmable line keys	<ul style="list-style-type: none"> • 9811: 2 • 9841: 4 • 9851: 46 • 9861: 130 • 9871: 128
Maximum of supported SIP lines	<ul style="list-style-type: none"> • 130 for CUCM and Webex DI • 16 for Webex Calling and Open SIP platforms
Hard keys	<ul style="list-style-type: none"> • Action button • Calendar button (9851 and 9861) • Favorite button • Hold/Resume key • Transfer key • Conference key (9841, 9851, 9861 and 9871) • Application key • Directory key (9841, 9851, 9861 and 9871) • Standard keypad • Volume-control toggle key • Speakerphone, Headset, and Mute keys • 2-way navigation key (9811) • 4-way navigation key (9841, 9851 and 9861) • Select key (9811, 9841, 9851 and 9861) • Home button (9871 only) • Page keys (9800 KEM only)

FEATURES	SPECIFICATIONS
Backlit indicator	<ul style="list-style-type: none"> • The phones support backlit indicator for the physical buttons of Speakerphone, Headset and Mute, Calendar (9851 and 9861), Select (9841, 9851 and 9861) and Home (9871 only) as well as the line keys. • The 9811 phone features a Front Arc LED that indicates device status, such as incoming calls, message waiting, missed calls, and more. The 9841, 9851, 9861 and 9871 phones are equipped with both a Front Arc LED and a Top 360 LED. These dual indicators provide clear status and notification alerts for personal devices and also display hot desk availability.
Handset	<ul style="list-style-type: none"> • The 9811 phone comes with a narrowband-capable audio handset by default, which connects via the phone's dedicated RJ-9 handset port. The wideband-capable handset used on other 9800 models is also compatible with the 9811 and can be purchased separately as an option. • The 9841, 9851, 9861, and 9871 phones come equipped with a wideband-capable audio handset (also connecting through the RJ-9 handset port) by default. • The handset coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm (about 1.8 ft)] coiled and up to 72 in. (183 cm (about 6 ft)) extended). • The handset is Hearing Aid-Compatible (HAC) and meets Federal Communications Commission (FCC Part 68) requirements for the Americans with Disabilities Act (ADA). You can achieve Section 508 loudness requirements by using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers.
Dial pad	<ul style="list-style-type: none"> • The dial pad is ADA-compliant.
Speakerphone	<ul style="list-style-type: none"> • The full-duplex speakerphone provides flexibility in placing and receiving calls handsfree. For added security, the audible Dual Tone Multifrequency (DTMF) tones are masked when the speakerphone mode is used.
USB and Aux port	<ul style="list-style-type: none"> • 9811: <ul style="list-style-type: none"> - One RJ-9 port for headset connection - One Auxiliary port for console log output • 9841: <ul style="list-style-type: none"> - One USB-A port: The USB-A port provides 0.25A power output at 5V or 1.25W under PoE, and 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). - One Auxiliary port (console log collection only). • 9851: <ul style="list-style-type: none"> - One USB-A port: The USB-A port provides 0.5A power output at 5V or 2.5W under PoE, and 1A power output at 5V or 5W when using the Cisco Power Adapter 3 (local power supply). - One USB-C port: The USB-C port provides 0.5A power output at 5V or 2.5W under PoE or when using the Cisco Power Adapter 3 (local power supply).

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • 9861 and 9871: <ul style="list-style-type: none"> - One USB-A port: The USB-A port provides 0.5A power output at 5V or 2.5W under PoE, and 1.3A power output at 5V or 6.5W when using the Cisco Power Adapter 3 (local power supply). - One USB-C port: The USB-C port provides 0.5A power output at 5V or 2.5W under POE or when using the Cisco Power Adapter 3 (local power supply). • 9800 KEM: <ul style="list-style-type: none"> - One USB-A female port: <ul style="list-style-type: none"> - When one 9800 KEM connected with the 9851, the USB-A port provides 0.15A power output at 5V or 0.75W under PoE, and 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). - When one 9800 KEM is connected with the 9861 or 9871, the USB-A port provides 0.15A power output at 5V or 0.75W under PoE, and 1A power output at 5V or 5W when using the Cisco Power Adapter 3 (local power supply). - When two 9800 KEMs are connected with the 9861 or 9871, the USB-A port provides 0.5A power output at 5V or 2.5W when using the Cisco Power Adapter 3 (local power supply). - When three 9800 KEMs are connected with the 9861 or 9871, the USB-A port provides 0.15A power output at 5V or 0.75W when using the Cisco Power Adapter 3 (local power supply). • One USB-A male port: The USB-A port on 9800 KEM draws power from the phone's USB-A port under PoE or when using the Cisco Power Adapter 3 (local power supply). • The charging capability depends on the maximum output power of the USB port on the phone in various deployment modes. If a connected device attempts to draw more power than the USB port's maximum output, a warning message will pop up, prompting you to unplug the device.
Ethernet switch	<ul style="list-style-type: none"> • 9811: An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network (IEEE 802.3i/802.3u) through an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. • An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. • The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.

FEATURES	SPECIFICATIONS
Bluetooth® wireless Technology*	<ul style="list-style-type: none"> • The 9861 and 9871 (excluding no-radio variants) feature Bluetooth wireless technology <ul style="list-style-type: none"> - Bluetooth version: 5.2 (Bluetooth® Low Energy) - Bluetooth Enhanced Data Rate (EDR) - Bluetooth Class 1 - Support for Wideband and Narrowband codecs - Bluetooth Profiles: <ul style="list-style-type: none"> Hands-Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) Human Interface Device Profile (HID) Phone Book Access Profile (PBAP)
Wi-Fi®	<ul style="list-style-type: none"> • The 9861 and 9871 (excluding no-radio variants) are Wi-Fi CERTIFIED™ supporting 802.11a/b/g/n/ac, 2.4 GHz / 5 GHz dual bands. • Authentication: <ul style="list-style-type: none"> - WPA (Wi-Fi Protected Access), WPA2 (Wi-Fi Protected Access II), and WPA3 (Wi-Fi Protected Access III) in both Personal and Enterprise modes - Extensible Authentication Protocol – Flexible Authentication via Secure Tunneling (EAP-FAST) - Protected Extensible Authentication Protocol – Generic Token Card (PEAP-GTC) - Protected Extensible Authentication Protocol – Microsoft Challenge Handshake Authentication Protocol Version 2 (PEAP-MSCHAPv2) - Extensible Authentication Protocol – Transport Layer Security (EAP-TLS) • Encryption: <ul style="list-style-type: none"> - Encryption Standard (AES) - Temporal Key Integrity Protocol (TKIP) and Message Integrity Check (MIC) • Advanced Robust management frame protection: BIP-CMAC-128 • Wi-Fi standards: <ul style="list-style-type: none"> - IEEE 802.11 a,b,d,e,g,h,i,n,r,ac - Wi-Fi MultiMedia (WMM) - Unscheduled Automatic Power Save Delivery (UAPSD) • Antenna Type: Dipole (On-Board) • Antenna Gain (dBi): <ul style="list-style-type: none"> - 9861: <ul style="list-style-type: none"> - 2.4G: 3:06 - 5G: 4.11 - 9871: <ul style="list-style-type: none"> - 2.4G: 3.22 - 5G: 4.23

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • Frequency Band (MHz) <ul style="list-style-type: none"> - 9861: <ul style="list-style-type: none"> - 2.4G: 2412.0 – 2472.0 - 5G: 5150.0 – 5250.0, 5250.0 – 5350.0, 5470.0 – 5725.0, 5745.0 – 5825.0 - 9871: <ul style="list-style-type: none"> - 2.4G: 2412.0 – 2472.0 - 5G: 5150.0 – 5250.0, 5250.0 – 5350.0, 5470.0 – 5725.0, 5745.0 – 5825.0 • Maximum EIRP for Mexico (dBm) <ul style="list-style-type: none"> - 9861: <ul style="list-style-type: none"> - 2.4G: 20.05 - 5G: 17.03 - 9871: <ul style="list-style-type: none"> - 2.4G: 20.19 - 5G: 17.21
Power	<ul style="list-style-type: none"> • IEEE Power over Ethernet class 2 (9811 and 9841) • IEEE Power over Ethernet class 3 (9851, 9861 and 9871) • Input rating: 0.42A, 48V DC • The phones are compliant with EU lot-6 and lot-26
Key Expansion Module (KEM) compatibility and power	<ul style="list-style-type: none"> • The 9800 KEM doesn't have its own local power; the KEM power is provided from the host phone. • 9851: <ul style="list-style-type: none"> - IEEE Power over Ethernet class 3 or Cisco Power Adapter 3, enables one KEM via the USB-A port. • 9861 and 9871: <ul style="list-style-type: none"> - IEEE Power over Ethernet class 3, enables one KEM via the USB-A port. - Cisco Power Adapter 3, enables up to three KEMs via the USB-A ports.

FEATURES	SPECIFICATIONS
<p>Key features</p> <p>(*may vary depending on registered calling platform)</p>	<ul style="list-style-type: none"> • Caller ID • Call waiting • Call hold/resume • Music on Hold (MoH) • Mute/unmute • E.164/Plus Dialing • Call forward • Do not disturb • Call back • Call park • Hold/Park Reversion • Call pickup • Transfer • Conference • Meet me • Call preservation mode • Speed dial • Busy Lamp Field (BLF) • Redial • Recording • Barge and cBarge (conference barge) • Paging* • Extension Mobility and EMCC* • Hunt group • Uniform Resource Identifier (URI) dialing • CMS mute sync* • Voicemail • Shared line • Privacy* • Local call history • Remote call history* • Directory search • Favorite contacts* • Adjustable ring tones and volume levels • Adjustable display brightness • Time and date display • Time zone settings* • E.911 • Intercom*

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • Confidential Access Level (CAL)* • Help desk on favorite button • Anti-spam* • Hoteling* • Flexible seating* • Voice feedback (multi-language support) • Webex features: unified call history, unified directory, hybrid calendar (not for 9811), meetings (not for 9811) • OBTP (One Button To Push) meetings (not for 9811) • In-meeting transcription (9861 and 9871) • In-call transcription (9861 and 9871) • Webex In-Meeting Summary (9861 and 9871) • Hot desking* (not for 9811) • Cisco Spaces Hot Desking pre-booking* (not for 9811) • Remote Reboot • Remote Factory Reset • Metrics for analytics and debugging* • Hotline* • XSI/XML Application • FAC/CMC* • Multicast Paging* • Support for Call center agent's phone* • Adjustable font size • Cisco IP Manager Assistant* • Switch the operating mode* • Custom wallpaper and logo (9851, 9861 and 9871) • Pagination* (9851 and 9861) • User Preference Attribute* • Cisco Headset Smart Pairing (9861 and 9871) • Mobility* • xAPI • Cisco Smart Power Framework • Always use multi-line mode (9811, 9841, 9851 and 9861) • Customizable New call softkey for connected call state* • Shared Call Appearance label config* • Dialog-based shared line appearance* • Enhanced menu customization* • Call Queues and Customer Assist support* • Reverse name lookup for Webex Personal Contacts* • Webex Companion (not for 9811) • Desk Phone Control (DPC) via Webex APP • Move call* • XSI call logs*

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • Minimum ringer volume enforcement* • Ringtone per line • MARI and FEC support • Quick access to Up and Down navigation keys • Abbreviated dial • PLAR*
Network features	<ul style="list-style-type: none"> • Session Initiation Protocol (SIP) for signaling • Session Description Protocol (SDP) • IPv4 and IPv6 • IPv6 Ready logo and USGv6 R1 compliant* • Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) • Dynamic Host Configuration Protocol (DHCP) client or static configuration • Gratuitous Address Resolution Protocol (GARP) • Domain Name System (DNS) • Trivial File Transfer Protocol (TFTP) • Secure HTTP (HTTPS) • VLAN • Real-Time Transport Protocol (RTP) • Real-Time Control Protocol (RTCP) • Cisco Discovery Protocol • LLDP (including LLDP Media Endpoint Discovery [LLDP-MED]) • Switch speed auto-negotiation • Span to PC • Network traverse (ICE, NAT and STUN)*
Deployment and serviceability features	<ul style="list-style-type: none"> • Native phone migration* • Peer firmware sharing upgrade • Problem report tool • ThousandEyes integration (9861 and 9871) • SRST support* • MRA support* • User credentials persistent for Expressway sign-in* • Activation code onboarding • WxC outbound proxy survivability support* • NFC onboarding (not for 9811) • Cisco headset upgrade (not for 9811) • Enhanced Control Hub Status and Desk Phone Diagnostics* • TR-069* • Option to postpone upgrades

FEATURES	SPECIFICATIONS
Security	<ul style="list-style-type: none"> • Secure boot • 802.1x with Custom Device Certificate • SIP OAuth • Secure credential storage • Device authentication • Configuration file authentication and encryption • Image authentication • Random bit generation • Secure Unique Device Identifier (SUDI) • Signaling authentication and encryption using TLS • Media authentication and encryption using SRTP • HTTPS for client and server • Configurable minimum TLS version • Local Phone Unlock Password* • Trusted Platform Module 2.0 • Security-Enhanced Linux • FIPS 140-2, 140-3 and UCR 2013 compliant • TLS 1.3 and TLS client/server min version • Secure erase • On device Firewall* • Assured Services SIP (AS-SIP)* • Multilevel Precedence and Preemption (MLPP)* • ECC* • Disabling speakerphone • Disabling headset, and handset* • Multi-server (SAN) Tomcat Certificate* • No password warning* • HTTP proxy* • VPN* (not for 9811) • Device Security Insights* • LLDP MED Location Information Service for E911* • HELD (E911) • Malicious Call Identification (MCID)
Physical dimensions (H × W × D)	<ul style="list-style-type: none"> • 9811: 8.2 x 7.9 x 1.9 in. (209.0 x 200.0 x 49.4 mm) • 9841: 8.4 x 8.4 x 1.9 in. (214.0 x 214.0 x 49.4 mm) • 9851: 8.9 x 8.4 x 1.9 in. (226.0 x 214.0 x 49.4 mm) • 9861: 8.9 x 9.0 x 1.9 in. (226.0 x 230.0 x 49.4 mm) • 9871: 8.9 x 8.4 x 1.9 in. (226.0 x 214.0 x 49.4 mm) • 9800 KEM: 8.9 x 5.0 x 1.9 in. (226.0 x 126.0 x 48.5 mm)

FEATURES	SPECIFICATIONS
Weight	<ul style="list-style-type: none"> • 9811: 849g • 9841: 954g • 9851: 968g • 9861: 1095g • 9871: 1055g • 9800 KEM: 483g
Phone-casing composition	<ul style="list-style-type: none"> • Polycarbonate Acrylonitrile Butadiene Styrene (ABS) textured plastic; Cosmetic class A
Operating temperature	<ul style="list-style-type: none"> • 32 to 104°F (0 to 40°C)
Nonoperating temperature shock	<ul style="list-style-type: none"> • 14 to 140°F (-10 to 60°C)
Humidity	<ul style="list-style-type: none"> • Operating 10 to 90%, noncondensing • Nonoperating 10 to 95%, noncondensing
Language Support	<ul style="list-style-type: none"> • Arabic (Saudi Arabia) • Bulgarian (Bulgaria) • Catalan (Spain) • Croatian (Croatia) • Czech (Czech Republic) • Danish (Denmark) • Dutch (Netherlands) • English (United Kingdom) • English (United States) • Estonian (Estonia) • Finnish (Finland) • French (France) • French (Canada) • German (Germany) • Greek (Greece) • Hebrew (Israel) • Hungarian (Hungary) • Italian (Italy) • Japanese (Japan) • Korean (Korea Republic) • Latvian (Latvia) • Lithuanian (Lithuania)

FEATURES	SPECIFICATIONS
	<ul style="list-style-type: none"> • Norwegian (Norway) • Polish (Poland) • Portuguese (Brazil) • Portuguese (Portugal) • Romanian (Romania) • Russian (Russian Federation) • Serbian (Republic of Serbia) • Simplified Chinese (China) • Slovak (Slovakia) • Slovenian (Slovenia) • Spanish (Colombia) • Spanish (Spain) • Swedish (Sweden) • Thai (Thailand) • Traditional Chinese (Hong Kong) • Traditional Chinese (Taiwan) • Turkish (Türkiye) • Ukrainian (Ukraine) • Welsh (United Kingdom)
Certification and compliance	<ul style="list-style-type: none"> • CE Markings per directives 2014/53/EU, 2014/35/EU and 2014/30/EU • Safety <ul style="list-style-type: none"> - UL60950, UL62368-1 - CAN/CSA-C22.2 No. 60950 CAN/CSA 62368-1 - EN/IEC 62368 - AS/NZS 62368 • EMC - Emissions <ul style="list-style-type: none"> - 47CFR Part 15 (CFR 47) Class B - AS/NZS CISPR 32 Class B - CISPR 32: 2015 Class B - EN 55032:2015+A11:2020 Class B - ICES 003 Class B - VCCI Class B - EN 61000-3-2 - EN 61000-3-3 - KS C 9832 - VCCI-CISPR 32

FEATURES

SPECIFICATIONS

- EMC - Immunity
 - EN 55035:2017+A11:2020 Class B
 - KS C 9835
 - Armadillo Light
- FIPS compliant
- Telecom
 - FCC Part 68, HAC
 - CS-03, HAC
 - AS/ACIF S004
 - AS/ACIF S040
 - NZ PTC 220
 - Industry Standards: TIA-810 and TIA-920
 - Industry Standards: IEEE 802.3 Ethernet, IEEE 802.3af and 802.3at
 - Korea (RRA Public Notification 2020-6, Sep. 25th, 2020)
 - Korea (RRA Announce 2022-1, Jan. 3, 2022)
- Radio
 - FCC Part 15.247
 - FCC Part 15.407
 - FCC Part 2.1091 (BT RF Exposure TR)
 - RSS-102 (BT RF Exposure TR)
 - RSS-247
 - EN 300 328
 - EN 301 893
 - EN 300 330
 - EN 62311
 - EN 50665
 - EN 301 489-1
 - EN 301 489-3
 - EN 301 489-17
 - Korea (KS X 3123:2022, KS X 3124:2020, KS X 3126:2020)
 - STD-T66
 - STD-T71

Ordering information

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION
Desk Phone 9800 Series Main Offer Summary	
DP-9811-K9=	Cisco Desk Phone 9811, NoNFC, Carbon Black
DP-9841-K9=	Cisco Desk Phone 9841, Carbon Black
DP-9841-L-K9=	Cisco Desk Phone 9841, First Light
DP-9851-K9=	Cisco Desk Phone 9851, Carbon Black
DP-9851-L-K9=	Cisco Desk Phone 9851, First Light
DP-9861-K9=	Cisco Desk Phone 9861, Carbon Black
DP-9861-L-K9=	Cisco Desk Phone 9861, First Light
DP-9861NR-K9=	Cisco Desk Phone 9861, No Radio, Carbon Black
DP-9871-K9=	Cisco Desk Phone 9871, Carbon Black
DP-9871-L-K9=	Cisco Desk Phone 9871, First Light
DP-9871NR-K9=	Cisco Desk Phone 9871, No Radio, Carbon Black
Desk Phone 9800 Series TAA Model Offer Summary	
DP-9811-K9+++	Cisco Desk Phone 9811, NoNFC, TAA, Carbon Black
DP-9841-K9+++	Cisco Desk Phone 9841, with NFC, TAA, Carbon Black
DP-9841NR-K9+++	Cisco Desk Phone 9841, No NFC, TAA, Carbon Black
DP-9851-K9+++	Cisco Desk Phone 9851, with NFC, TAA, Carbon Black
DP-9851NR-K9+++	Cisco Desk Phone 9851, No NFC, TAA, Carbon Black
DP-9861-K9+++	Cisco Desk Phone 9861, TAA, Carbon Black
DP-9861NR-K9+++	Cisco Desk Phone 9861, No Radio, TAA, Carbon Black
DP-9871-K9+++	Cisco Desk Phone 9871, TAA, Carbon Black
DP-9871NR-K9+++	Cisco Desk Phone 9871, No Radio, TAA, Carbon Black

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION
Desk Phone 9800 Series Customized Model Offer Summary	
DP-9811-K9---=	Cisco Desk Phone 9811, NoNFC, Customized Model, Carbon Black
DP-9841-K9---=	Cisco Desk Phone 9841, Customized Model, Carbon Black
DP-9841NR-K9---=	Cisco Desk Phone 9841, NoNFC, Customized Model, Carbon Black
DP-9851-K9---=	Cisco Desk Phone 9851, Customized Model, Carbon Black
DP-9851NR-K9---=	Cisco Desk Phone 9851, NoNFC, Customized Model, Carbon Black
DP-9861-K9---=	Cisco Desk Phone 9861, Customized Model, Carbon Black
DP-9861NR-K9---=	Cisco Desk Phone 9861, NoRadio, CustomizedModel, CarbonBlack
DP-9871-K9---=	Cisco Desk Phone 9871, Customized Model, Carbon Black
DP-9871NR-K9---=	Cisco Desk Phone 9871, NoRadio, CustomizedModel, CarbonBlack
Desk Phone 9800 Series Arabic Model Offer Summary	
DP-9861-A-K9=	Cisco Desk Phone 9861, Arabic Layout, Carbon Black
DP-9871-A-K9=	Cisco Desk Phone 9871, Arabic Layout, Carbon Black
Desk Phone 9800 Series Accessories (Optional - Ordered Separately)	
DP-9800-KEM=	Cisco Desk Phone 9800 Key Expansion Module, Carbon Black
DP-9800-WMK=	Cisco Desk Phone 9800 Wall Mount Kit
DP-9800-KEM-WMK=	Cisco Desk Phone 9800 Wall Mount Kit for Key Expansion Module
DP-9800-WMK-88ADP=	Cisco Desk Phone 9800 Wall Mount Kit Adapter for 8800 Phones
Desk Phone 9800 Series Local Power SPAREs (Optional - Ordered Separately)	
CP-PWR-ADPT-3-AR=	Cisco Power Adapter 3 with Argentina Clip
CP-PWR-ADPT-3-AU=	Cisco Power Adapter 3 with Australia Clip
CP-PWR-ADPT-3-BZ=	Cisco Power Adapter 3 with Brazil Clip
CP-PWR-ADPT-3-CN=	Cisco Power Adapter 3 with China Clip
CP-PWR-ADPT-3-EU=	Cisco Power Adapter 3 with European Clip
CP-PWR-ADPT-3-IN=	Cisco Power Adapter 3 with India Clip

Table 4. Ordering information

PART NUMBER	PRODUCT DESCRIPTION
CP-PWR-ADPT-3-KR=	Cisco Power Adapter 3 with Korea Clip
CP-PWR-ADPT-3-NA=	Cisco Power Adapter 3 with North America Clip
CP-PWR-ADPT-3-UK=	Cisco Power Adapter 3 with United Kingdom Clip
Desk Phone 9800 Series Replacement SPAREs	
DP-9800-HS=	Desk Phone 9800 Replacement Handset, Carbon Black - SPARE
DP-9800-HS-L=	Desk Phone 9800 Replacement Handset, First Light - SPARE
DP-9800-CORD=	Desk Phone 9800 Replacement Handset Cord, Carbon Black - SPARE
DP-9800-CORD-L=	Desk Phone 9800 Replacement Handset Cord, First Light - SPARE
DP-9811-FS=	Desk Phone 9811 Replacement Footstand, CarbonBlack - SPARE
DP-9800-FS=	Desk Phone 9841 & 9851 Replacement Footstand, Carbon Black - SPARE
DP-9861-FS=	Desk Phone 9861 Replacement Footstand, Carbon Black - SPARE
DP-9871-FS=	Desk Phone 9871 Replacement Footstand, Carbon Black - SPARE

Table 5. Package Dimensions, Weights and Piece Counts

PRODUCT	GIFTBOX				OVERPACK					PALLET					
	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Box pcs per overpack	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Over pack pcs per pallet	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Phones/ Accessories per Pallet
9811	28.1	23.6	7.2	1.3	8	60.1	29.4	25.5	10.8	24	121.9	101.6	114.7	234.2	192
9841	31.5	24	7.8	1.3	10	50	40	34	14.3	18	120	100	114	275	180
9851	31.5	24	7.8	1.4	10	50	40	34	14.4	18	120	100	114	276.2	180
9861	31	24.5	7.2	1.5	8	60.1	32.1	26.4	12.9	24	121.9	101.6	117.5	332.6	192
9871	29.1	24.5	7.2	1.5	8	60.1	30.4	26.4	12.7	24	121.9	101.6	117.5	327.8	192
9800 KEM	25.4	17.3	8.13	0.71	18	54	50.42	28.45	13.3	12	121.9	101.6	99.7	182.6	216
9800 WMK (Phone)	26.5	17.5	4	0.63	30	56	45	29	19	20	122	101	160	398.5	600
9800 KEM WMK	32	11	2.8	0.5	15	48	33	13	7.23	60	110	98	145	434	900

Licensing

All Cisco Desk Phone 9800 Series are covered by the Cisco End User License Agreement at www.cisco.com/c/en/us/about/legal/cloud-and-software/end_user_license_agreement.html.

Or use the shortcut: www.cisco.com/go/eula.

Warranty information

The Desk Phone 9800 Series are covered by a Cisco 1-Year Limited Hardware Warranty (details at: www.cisco.com/go/warranty).

Product sustainability

Information about Cisco's Environmental, Social and Governance (ESG) initiatives and performance is provided in Cisco's CSR and sustainability [reporting](#).

Table 6. Cisco Environmental Sustainability Information

SUSTAINABILITY TOPIC	REFERENCE
Information on product-material-content laws and regulations	Materials
Information on electronic waste laws and regulations, including our products, batteries, and packaging	WEEE Compliance

Table 7. Product Sustainability Features and Certifications

FEATURES	SPECIFICATIONS
Energy Saving Solutions	<ul style="list-style-type: none"> • The phones support the display off (not for 9811) and deep sleep modes. • Display off mode power consumption: <ul style="list-style-type: none"> - 9841: 2.35W when using the Cisco Power Adapter 3 (local power supply) and 1.95W under PoE - 9851: 2.82W when using the Cisco Power Adapter 3 (local power supply) and 2.69W under PoE - 9861: 3.48W when using the Cisco Power Adapter 3 (local power supply) and 3.26W under PoE - 9871: 4.03W when using the Cisco Power Adapter 3 (local power supply) and 3.6W under PoE • Deep sleep mode power consumption: <ul style="list-style-type: none"> - 9841: 0.26W when using the Cisco Power Adapter 3 (local power supply) and 0.61W under PoE - 9851: 0.27W when using the Cisco Power Adapter 3 (local power supply) and 0.69W under POE - 9861: 0.27W when using the Cisco Power Adapter 3 (local power supply) and 0.79W under PoE - 9871: 0.23W when using the Cisco Power Adapter 3 (local power supply) and 0.8W under PoE
Carbon Emission Insights	<ul style="list-style-type: none"> • The phones support to report the power consumption data and the organization's carbon footprint can be shown on the Cisco Webex Control Hub.
Certification and compliance	<ul style="list-style-type: none"> • ENERGY STAR® • EU Lot-6 • EU Lot-26

Cisco Capital

Flexible payment solutions to help you achieve your objectives.

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services, and complementary third-party equipment in easy, predictable payments. [Learn more.](#)



For more information

Please visit <https://www.webex.com/cisco-phone-9800series.html>.

Date: March 2026

C78-4253749-06